

Data sheet

SM M22 - Digital Output (M22-1HF10)

Technical data

| | |
|---|--------------------------------|
| Order no. | M22-1HF10 |
| Type | SM M22 - Digital Output |
| Module ID | 0115 AFC8 |
| General information | |
| Note | - |
| Features | 8x DO AC 230 V 2 A relay |
| Current consumption/power loss | |
| Current consumption from backplane bus | 140 mA |
| Power loss | 1.5 W |
| Technical data digital outputs | |
| Number of outputs | 8 |
| Cable length, shielded | 1000 m |
| Cable length, unshielded | 600 m |
| Rated load voltage | DC 30 V/ AC 230 V |
| Current consumption from load voltage L+ (without load) | - |
| Total current per group, horizontal configuration, 40°C | 4 A |
| Total current per group, horizontal configuration, 60°C | 4 A |
| Total current per group, vertical configuration | 4 A |
| Output current at signal "1", rated value | 2 A |
| Signal logic output | Isolated |
| Output delay of "0" to "1" | 10 ms |
| Output delay of "1" to "0" | 5 ms |
| Minimum load current | - |
| Lamp load | - |
| Parallel switching of outputs for redundant control of a load | not possible |
| Parallel switching of outputs for increased power | not possible |
| Actuation of digital input | - |
| Switching frequency with resistive load | max. 0.33 Hz |
| Switching frequency with inductive load | max. 0.33 Hz |
| Switching frequency on lamp load | max. 0.33 Hz |
| Internal limitation of inductive shut-off voltage | - |
| Short-circuit protection of output | - |
| Trigger level | - |
| Number of operating cycle of relay outputs | - |
| Switching capacity of contacts | 5 A |
| Output data size | 8 Bit |
| Status information, alarms, diagnostics | |
| Status display | green LED per channel |
| Interrupts | no |
| Process alarm | no |
| Diagnostic interrupt | no |

| | |
|----------------------------------|-----------|
| Diagnostic functions | no |
| Diagnostics information read-out | none |
| Supply voltage display | green LED |
| Group error display | red LED |
| Channel error display | none |

Isolation

| | |
|------------------------------------|-----------|
| Between channels | - |
| Between channels of groups to | 2 |
| Between channels and backplane bus | yes |
| Insulation tested with | AC 2200 V |

Datasizes

| | |
|------------------|---|
| Input bytes | 0 |
| Output bytes | 1 |
| Parameter bytes | 0 |
| Diagnostic bytes | 0 |

Housing

| | |
|----------|--------------------|
| Material | PPE / PPE GF10 |
| Mounting | Profile rail 35 mm |

Mechanical data

| | |
|------------------------------|-----------------------|
| Dimensions (WxHxD) | 26 mm x 88 mm x 71 mm |
| Net weight | 110 g |
| Weight including accessories | 110 g |
| Gross weight | 123 g |

Environmental conditions

| | |
|-----------------------|-----------------|
| Operating temperature | 0 °C to 60 °C |
| Storage temperature | -25 °C to 70 °C |

Certifications

| | |
|------------------|-----|
| UL certification | yes |
| KC certification | yes |