

e-med^{ic}™ Tablet 8"

Unlimited
Mobility



The e-med^{ic}™ Tablet 8" opens a new world in daily medical business. With the 8 inch tablet, e-mails, messages, photos and information are everywhere available. The included e-med^{ic}™ medical docking station offers the possibility to load your tablet at a designated place. In addition, the docking station offers further interfaces for a second monitor, a mouse and a keyboard. This allows continue working, comfortably while your e-med^{ic}™ Tablet is loading.

If you want to use the docking station in the patient environment, it is necessary to connect a network isolator. We recommend the network isolator MED MI 1005 item no.: 2005674.

Benefits:

- › Sturdy – Shockproof – Drop-Resistant
- › Operable with gloves
- › IP65 housing – dirt- and splash-proof
- › Closed, disinfectable housing
- › Drop-resistant up to 1 metre
- › height – Gorilla Glass
- › Docking station with quick-charging function via docking pins (3A)
- › Docking station Compatible with optinal Drop Case



e-medTMic

MEDICAL COMPUTER HARDWARE



Docking station -
compatible to e-medTMic Tablet 8"/ 10"



e-medTMic Tablet 10

Technical Data e-medTMic Tablet 8" - Docking Station include

Processor	Intel® Atom™ Z3795
Compatibles OS	Windows® 10 Pro (extra fee)
Display	8,3" (21,08 cm); IPS Sunlight Readable Outdoor-Display
Resolution	1.920 x 1.200 Pixel (WUXGA)
Contrast	1.000:1
Brightness	500 cd/m ²
Display glass	Gorilla®-Glas 3
Graphics	Intel® HD Graphics
Touch	Multi-Touch (10 finger); capacitive
RAM	4 GB LPDDR3
Hard disk	64 GB eMMC
Features	GPS, GLONASS, NFC (depending on the OS used), µSD card slot, WLAN IEEE 802.11 a/b/g/n, Bluetooth 4.0 + HS; Card Reader microSDXC, Kensington Lock
Optional	via Back-Cover-Extension: Smart Card Reader, Barcode Reader Drop Case up to 1,80 m, Windows® 10 Pro 64-bit, LTE
Interface	1x USB 2.0, 1x microUSB, 1x Mic-in, Docking-Plug
Interfaces Docking station	3x USB 3.0, 1x HDMI, 1x RJ45 (10/100/1000 MBit/s)
Camera	Front: 2,0 Megapixel ; Rear: 8,0 Megapixel
Battery	Li-Po, up to 10 h run time
Protection class	IP 65
Power supply	external
Weight	0,554 kg
Dimensions (BHT)	227,8x 150,1x 12,5 mm
Standards	DIN EN 60601-1-2:2015, DIN EN 61000-3-2:2006 +A1:2009+A2:2009, DIN EN 60950-1:2006 +A11:2010+A1:2010+A12:2011:A2:2013, DIN EN 55011:2009 + A1:2010(limit class B), DIN EN 61000-3-3:2008, (DIN EN 60601-1 3.1 Edition- only power supply)
Item No.	2011894